

SECTION IV	OCCUPATIONAL EXPOSURE LIMITS
No OSHA/PEL or ACGIH/TLV has been established.	

SECTION V	EMERGENCY AND FIRST AID PROCEDURES
<p>Eye Contact : flush eyes with water if irritation occurs.</p> <p>Skin Contact : if contact with molten product occurs. treat as for thermal burn.</p> <p>Inhalation : not ordinarily required.</p> <p>Ingestion : not ordinarily required.</p>	
<p>NFPA RATINGS(SCALE 0-4) :</p> <p>Health = 1 Fire = 1 Reactivity = 0</p>	

SECTION VI	SUPPLEMENTAL INFORMATION
None identified	

SECTION VII	PHYSICAL DATA				
BOILING POINT (°C)	N.A	MELTING POINT (°C)	160 - 165	VAPOR PRESSURE (mmHg)	N.A
SPECIFIC GRAVITY	0.90-0.92	% VOLATILE BY VOLUME	N.A	VAPOR DENSITY	N.A
SOLUBILITY IN WATER	insoluble	EVAPORATION RATE (BUTYLACETATE 1)	N.A	N.A = Not Applicable	
<p>APPEARANCE AND ODOR</p> <p>Solid essentially colorless and odorless pellet.</p>					

SECTION VIII	FIRE AND EXPLOSION HAZARDS		
FLASH POINT AND METHOD USED	FLAMMABLE LIMITS % VOLUME IN AIR	LOWER	UPPER
N.A	N.A		
<p>EXTINGUISHING MEDIA</p> <p>Use water fog, foam, dry chemical or CO2</p>			
<p>SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS</p> <p>Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.</p>			
<p>UNUSUAL FIRE AND EXPLOSION HAZARDS</p> <p>Treat as a solid that can burn. Molded parts generally burn slowly with a low smoke density and flaming drips. Under certain conditions can burn with a high smoke density.</p>			

SECTION IX		REACTIVITY	
STABILITY <input type="checkbox"/> UNSTABLE <input checked="" type="checkbox"/> STABLE		HAZARDOUS POLYMERIZATION <input type="checkbox"/> MAY OCCUR <input checked="" type="checkbox"/> WILL NOT OCCUR	
CONDITIONS AND MATERIAL TO AVOID Strong oxidizing agents			
HAZARDOUS DECOMPOSITION PRODUCTS At processing temperature, some degree of thermal degradation will occur ; although highly dependent on temperature and environmental conditions, a variety of decomposition products may be present ranging from simple hydrocarbons(such as methane and propane) to toxic/irritating gases (carbon monoxide and dioxide, acrolein, acids, ketones, aldehydes) ; see SPECIAL PRECAUTIONS			

SECTION X		EMPLOYEE PROTECTION	
RESPIRATORY PROTECTION Not ordinarily required.			
PROTECTIVE CLOTHING Not ordinarily required.			
ADDITIONAL PROTECTIVE MEASURES Adequate ventilation and/or engineering controls are required when product is heated in processing.			

SECTION XI		ENVIRONMENTAL PROTECTION	
SPILL OR LEAK PROCEDURES Shovel and sweep up or use industrial vacuum cleaner : avoid generating dust clouds : put into containers for reclaiming or disposal.			
WASTE DISPOSAL Place in an appropriate disposal facility in compliance with local regulations.			
ENVIRONMENTAL HAZARDS N.A			

SECTION XII		SPECIAL PRECAUTIONS	
Treat as a solid that can burn. Store away from oxidizing materials, in a cool, Dry place with adequate ventilation : bond and ground transpire equipment. Avoid vapors from heated products. Adequate ventilation and/or engineering controls must be employed in high temperature processing to prevent exposure to potentially toxic/irritating fumes.			